

## CEROTECT M2

Cold applied bituminous protective coating.

### Description:

- **CEROTECT M2** is cold applied protective damp proofing or water proofing bituminous coating.
- **CEROTECT M2** is a blend of selected bitumen and solvents which dries to form a high quality bituminous film.

### Fields of Use:

- Water proof coating for all types of concrete and masonry structures.
- Protective coating, for foundations and under ground structures.
- Anti – rust coating for steel structures.

### Advantages:

- Cold applied, easy to use.
- Single component.
- Excellent adhesion properties to most of building materials surfaces.
- High coverage rate.
- High resistance to aggressive salts in soil.
- Low cost compared with traditional hot applied bituminous materials.

### Technical Data : (at 25 °C)

Water content (%)	0 %
Density	0.90 ± 0.05 (kg/L)
Total bitumen content	70 – 80 %
Ash, max	0.5 %
Solvent	naphtha (5 – 10 %) if required
Theoretical Coverage	200 g/m <sup>2</sup> for 150 micron thickness in case of concrete apply primer coat diluted with 15% naphtha.

### Directions for Use:

- The surfaces should be properly cleaned.
  - Stir **CEROTECT M2** before use. (Add naphtha max 10% if required)
  - **CEROTECT M2** can be applied using brushes, rollers or sprayers.
  - The number of coats and the rate of use depends upon the purpose of use and the required thickness.
- \*\*Not: for concrete surfaces apply primer coat diluted with 15% naphtha

### Storage:

- 6 months under suitable storage conditions.

### Packages:

- 1 kg , 4 kg , 15 kg and 125 kg drums.