

CRACK TAPE

Self-Sticking Fiber Glass Tape For Joints And Wall Repair

DESCRIPTION:

CRACK TAPE : is a fiberglass mesh tape, self-sticking to different surfaces for joints , cracks and holes repair.

FIELDS OF USE:

Repair small cracks in walls and ceilings.
Joints between all kinds of boards as wood, gypsum , foam ... etc
Patching holes smaller than tape width.

ADVANTAGES:

Excellent fiberglass reinforcement for places close to holes and cracks.
No need to adhesives for its self-sticking property.
Saving time and labour.
Prevents the cracks from reappearing.
Good finish for joints in wall boards.
Receive all finishing putty and paints.

DIRECTIONS FOR USE:

a- BOARD JOINTS

- 1- Surface closed to joints should be cleaned and free from dust, oil and grease.
- 2- Unroll tape over joints , pressing down firmly to ensure proper adhesion from top to bottom for easier handling.
- 3- Cut with scissors or a cutter blade.
- 4- Apply the putty ensure that it penetrates through tape and to dry.
- 5- Complete paint or decoration works.

b-PLASTER CRACKS

- 1- Remove paints and previous putty closed to crack path to be repaired , in a width of tape . (2.5 cm each side of crack for 5 cm tape width).
- 2- Unroll tape over crack - in the same steps as in a - board joints. Steps (2-4).
- 3- Complete paint or top layer with KEMAXIT 200.

c- HOLES

- 1- Surface closed to holes, should be cleaned and free from dust, oils
- 2- Unroll two perpendicular layer of tape with length 3 cm more than hole width in each side.
- 3- Apply the same procedure as in a - board joints step (4-5).

DIMENSIONS:

Roll 90 meters x 5 cm.

