

## Kemcrack

Elastic Crack Putty.

### Description:

- **KEMCRACK** is a one component ready to use elastic putty, based on acrylic emulsion.
- Complies with CMBI TECH.SPCS. No. CMBI 7060

### Fields of Use:

- Filling cracks in cementitious surfaces and building elements for exterior and interior uses.
- Filling joints between aluminum, wooden windows, doors and plaster.

### Advantages:

- Fast drying.
- Easy to use.

### Technical Data : (at25 °C)

Colour	White
Solids ratio (wt)	77±1%
Density	1.45 ± 0.05 kg/l
PH - value	7.5 - 8.5
Drying time	60 minutes
Viscosity	120 ±10
Rate of use	2.0 kg /l

### Directions for Use:

- Cracks should be completely cleaned with air pressure - Also the dust, grease, oils any loose materials should be removed.
- Cracks should be filled with **KEMCRACK** using a trowel.
- In case of narrow and hair cracks, it is advisable to widen them till about 3mm.
- Refill the crack with **KEMCRACK**.
- Don't add any water to **KEMCRACK** before use.
- Clean tools directly after use with water.

### Safety Precautions:

- Wear gloves and goggles.
- Skin and face contamination should be washed with water and soap.
- Accidental splashes to eyes must be rinsed with clean water and then report to specialist.
- Do not eat and smoke during use.

### Storage:

- 12 months in closed packages, in dry and shaded areas.

### Packages:

- 1 kg, 5 kg and 25 kg.