Kemstone

Decorative, Durable, multi - Coloured, Textured Finish For Interior and Exterior Use

Description:

- KEMSTONE: is a ready to apply decorative plaster composed of a mixture of natural coloured sand and high quality modified acrylic binder.
- · Complies with CMBI TECH. SP.CS. no CMBI 7030.
- Available in two different types:- KEMSTONE 1000 (spherical granules) and KEMSTONE 2000 (angular granules).

Fields of Use:

- Exterior and interior finish for different surfaces like concrete, masonary, stone, plaster, gypsum boards and wood.
- Suitable for office building, hotels, hospitals, schools, public and private buildings, shops and dwelling buildings.

Advantages:

- Available in a highly attractive variety of colour patterns.
- Is washable and highly resistant to abrasion. It could be applied indoors and outdoors.
- Flexible and has excellent adhesion on concrete surfaces, cement plaster, wood steel etc.
- · Does not require surface preparation and priming prior to application.
- · Has a guaranteed durability, it does not chip, flake or peel even after many years.
- Provides a smooth or textured finish that covers holes, cracks and other surface defects, which a thin paint can not hide.
- · Has excellent water, acid and alkali resistance.
- · Vapour permeable
- Easy to apply in one low cost operation using trowel, roller or sprayer.
- · Has a high coverage rate.
- · Is very economic.

Technical Data: (at 25° C)

Colour One colour or some colours interfered

Density $1.75 \pm 0.05 \text{ kg/l}$ PH 7.5 - 8.5 Viscosity $45 \pm 5 \text{ Pois}$

Rate of use $2 - 3 \text{ kg} / \text{m}^2 (4.0 \text{ kg} / \text{m}^2 \text{ for spray})$

Directions for Use:

- **KEMSTONE** is ready to use and applied just like a plaster coating with a plasters trowel. It can be used directly on all sound and dry surfaces. It is however, recommended to prime plaster and porous substrates with one coat of **ADDIBOND** diluted 1:5 with water.
- Sprayer should be used for some kinds of this product as indicated on the pails of **Kemstone 2000**.
- · Clean tools directly after use with water.

Safety Precautions:

- · Wear gloves and goggles.
- · Skin and face contamination should be washed with water.
- · Accidental splashes to eyes must be rinsed with clean water and then report to a specialist.
- · Do not eat or smoke during use.

Storage:

• 9 months (in closed containers) under suitable storage conditions.

Packages:

• 1 kg, 5 kg, 18 kg and 125 kg.

