

## KEM PRIMER

Red Oxide

### Description:

- KEMPRIMER is an anticorrosive primer containing high quality red ironoxides and resins, which ensures good adhesion to metallic surfaces and also to nitrocellulose and other paints.

### Fields of use:

- An anticorrosive primer suitable for application on all steel and iron surfaces e.g. cars, steel structure like beams, angles, fences, doors, windows etc.

### Advantages:

- Ready to use and does not required skilled labour.
- Needs no thinner for application.
- An homogenous liquid, that contains a stable and constant concentration of the active ingredients.
- Excellent adhesion to the substrate, durable and weather resistant.

### Technical Data :(at 25 °C)

Gloss	Matt
Solid Content	60 %
Density	1.38 ± 0.02 kg/L
Viscosity FC/4	80 - 100 seconds
Surface drying	not less than 2 hours
Hard drying	not more than 24 hours
DFT	60 microns
WFT	100 microns
Thinner	KEMSOLVE 7

### Directions for use:

- The surface of steel should be clean, free from oils and grease.
- Remove rust by wire brushing or sand blasting.
- Apply one coat of primer when nitrocellulose paints or other topcoats to be used.
- It is recommended to use a second coat to primer when no further top coats are to be used.

### Rate of use:

- 1 kg, covers from 6 -8 m<sup>2</sup> according to the type and condition of the surface per each coat.

### Precautions:

- Application should be carried out in a well ventilated place.
- Gloves, protective lothing and eye goggles should be worn during application.
- Skin contaminations should be immediately washed with soap and plenty of water.
- If the material is splashed into the eyes, these should be immediately washed with water, and then report to an specialist.
- Do not eat or smoke during use.

### Storage / Shelf life:

- 3 years under suitable storage conditions.

### Packages:

- 0.25 kg, 1.0 kg, 5 kg. and 20 kg .