

ZETOLAN W

Wax – based chemical release agent for concrete shuttering

DESCRIPTION:

- ZETOLAN W is a carefully blended combination of high quality wax and emulsifying agents, which enables a stable film of wax to be coated on form work allowing fast and easy stripping.

FIELD OF USE:

- Can be used with all types of moulds and concrete shutterings.

ADVANTAGES:

- Ensures a high quality stain free concrete and reduce the incidence of blow holes.
- Can be used for all types of moulds and concrete shutterings.
- Minimizes cleaning of shuttering and lengthens its life. It protects against water penetration and deterioration , and protect steel against corrosion.
- Is inflammable and without physiological effects, so can be used in closed areas.
- Saves time and money.

TECHNICAL DATA:

Density	0.75	0.05 kg/ L at 25°C
Flash point	none	
Coverage rate	20 - 30 m ² / L on wood.	
(depending on used tool)	40 - 60 m ² / L on metal.	

DIRECTIONS FOR USE:

- For new shuttering no preparation of the surface is required. However,ensure that shutters are clean before application.
- For used shuttering , all traces of cement and previously used from oils must be removed.
- ZETOLAN W is applied by brush , roller, sprayer or sponge in the form of a uniform thin coating prior to concreting.
- On metal, glass-fiber or any other surface , one coat of ZETOLAN W should be applied before concrete placing.

STORAGE:

- 5years under suitable storage conditions .

PACKAGES :

- 20 , 210 litre drums.