



CMB 2000

Ready-to-use, cold applied asphalt mix for quick road repairs in.

Description:

- Ready-to-use homogeneous asphalt mix composed of specially processed asphalt and carefully selected filler materials, cold applied.

Fields of Use:

- Repairing concrete and asphalt roads, as well as roads made of paving tiles and bricks.
- Parking areas and railway crossings.
- Can be used on metal and wooden surfaces, as well as on dry and wet surfaces.

Advantages:

- Cold applied, environmentally friendly.
- Ready mix for permanent immediate repairs.
- Quick drying, high durability, and no need for preparatory treatments.
- Easy to use with a shovel only and requires no specialized labor.
- Allows for immediate road access without sticking to vehicle tires.

Technical Data: (25 °C)

Adhesion with asphalt:	Excellent
Adhesion with concrete	Excellent
Adhesion with asphalt bricks:	Excellent
Adhesion with rubber:	Does not adhere
Rate of use:	100 kg/m ² / 5cm thickness

Directions for Use:

- Clean the holes from previous debris and compact the ground well.
- Fill with CMB 2000 material in layers of 5-7 cm thickness, compacting each layer thoroughly, and shape the final layer with a slight arch upwards, then compact it with the back of the shovel until the surface is level.

Storage / shelf life : Two years under suitable storage conditions and in its sealed packaging.

Packages: 20Kg

