

Acryl Flex 200

Highly-flexible, waterproofing and heat reflective liquid membranes.

Description :

- **Acryl Flex 200** is a high flexible acrylic emulsion and special additives, produced especially for a waterproofing and reflective layer of insulation.

Fields of Use :

- waterproofing of concrete, wood and cement tile surfaces of unused roofs that have suitable inclinations towards rain drainage gutters.

Advantages :

- Resist the fungal growth.
- Barrier against salts and atmospheric gases.
- Resist UV.
- Anti- carbonation of concrete.
- Can be reinforced with fiberglass or polyester fabric between layers of paint for strengthening.

Technical Data :(at 25° C)

- | | |
|-----------------|-----------------------------|
| • Color | white |
| • Density | 1.33 ± 0.02 (kg/liter) |
| • Viscosity | 12 ± 2 poise |
| • Solid content | 62 % ± 1 % |
| • PH | 8 - 9 |
| • Rate of use | 500 - 600 gm/m ² |

Direction for use :

- Water proofing must be performed on strong , clean surfaces after treatment the intersection of vertical and horizontal surfaces and any other defects with addipond 65 mortar. As well as taking into account slopes towards drainage gutters.
- Surface to be painted must be free from dust, oil grease and disconnected or weak parts.
- Apply one coat of **Acryl flex 200** diluted with water by 1 : 3 by volume.
- Apply **Acryl flex 200** using the brush or roller ,then put fabric and press it using the roller.
- Apply the second coat after a few hours of the first coat according to the temperature and humidity. It is preferable to apply the second coat perpendicular to the first coat.
- Take into account that the insulation continues on a vertical skirting of 20 - 30 cm high.
- All tools should be cleaned with water after use.

Storage/shelf life:

- For 12 months under proper storing conditions.

Packages:

- 4 kg , 15 kg.