

CEROTECT M2

Cold applied bituminous protective coating.

Description:

- CEROTECT M2 is cold applied protective damp proofing or water proofing bituminous coating.
- CEROTECT M2 is a blend of selected bitumen and solvents which dries to form a high quality bituminous film.
- Complies with CMB Technical Spec. No. 9080.

Fields of Use:

- Water proof coating for all types of concrete and masonry structures.
- Protective coating, for foundations and under ground structures.
- Anti – rust coating for steel structures.

Advantages:

- Cold applied, easy to use.
- Single component.
- Excellent adhesion properties to most of building materials surfaces.
- High coverage rate.
- High resistance to aggressive salts in soil.
- Low cost compared with traditional hot applied bituminous materials.

Technical Data : (at 25 °C)

Water content (%)	0 %
Density	0.90 ± 0.05 (kg/L)
Total bitumen content	65 : 75 %
Ash, max	0.5 %
Solvent	H/T or naphtha (5–10 %) if required
Theoretical Coverage	200 g/m ² for 150 micron thickness in case of concrete apply primer coat diluted with 15% naphtha.

Directions for Use:

- The surfaces should be properly cleaned.
 - Stir CEROTECT M2 before use. (Add naphtha max 10% if required)
 - CEROTECT M2 can be applied using brushes, rollers or sprayers.
 - The number of coats and the rate of use depends upon the purpose of use and the required thickness.
- **Not: for concrete surfaces apply primer coat diluted with 15% naphtha

Storage / Shelf life:

- 6 months under suitable storage conditions.

Packages:

- 1 kg , 3 kg , 15 kg and 120 kg drums.