

CEROTEKT S

**A Silvered Bituminous Roof Insulation
Coating Heat And Light Reflecting**

DESCRIPTION :

- CEROTEKT S is a protective coating easily applied to any roofing surface of any shape and complexity .

ADVANTAGES :

- Provides a reflective and anti-solar film, which reduces heat absorption, ultra violet ray effects and weathering attacks .
- Provides a durable and aesthetically pleasing silver finish .
- Is very economic .

TECHNICAL DATA :

| | |
|---------------------------|--------------------------|
| Base | Modified bitumen |
| Soild content | 45 % |
| Colour | Sliver |
| Density | 1.00 ± 0.05 kg/ L . |
| Surface temperature range | - 40 to + 140 °C |
| Hardening time | Hardens after 3-7 days . |

DIRECTIONS FOR USE :

- Stir CEROTEKT S before use .
- CEROTEKT S is easily applied by roller, brush or sprayer to any roof surface and is especially suitable on felt, asphalt and other bituminous layers .
- Application tools are to be cleaned with kerosine .

RATE FOR USE :

- 1 kg covers 8-10m² .
- One coat of CEROTEKT S is usually enough .

STORAGE LIFE :

- 12 months under suitable storage conditions .

PACKAGES :

- 15 kg .