LEYCO - SEAL 22

High - Gloss long Lasted Polymer Seal

DESCRIPTION:

- LEYCO-SEAL 22 is a metal cross-linked synthetic dispersion with high pressure emulsified polythenes.
- The non slip water-proof protective film is characterized by an extereme resistance, soil repulsion and exceptional waer resistence as well as being long lasting . It forms the ideal foundation for the high-speed process and makes daily maintainance easier. The application of LEYCO-SEAL 22 reduces significantly rubber marks from froklift or
- car tires on coated or non-coated industrial floors in warehuses, stores and foot marks on any kind of floors.
- Increases the surfaces hygiene.

FIELDS OF APPLICATION:

All surfaces except unsealed textile flooring and parquet.

ADVANTAGES:

- Produces a high-gloss protective film, hard as steel .
- Exremly wear resistant and long lasting.
- Reduces significantly rubber marks from forklift and shoes.
- Film with large soil-repulsion .
 Metal cross-linked acrilic with innovatives polythenes .
- High solid percentage.
- Ideal for manual application and high speed process.

TECHNICAL DATA:

1.02 g/cm3 Density colour milky, white

PH-value

Rate of use 6 - 8 m²/ L (depends on quality and porosity of

surfaces and the desired gloss.

APPLICATION:

- AS PRIMER: Floor must be stripped.
- If necessary clean with LEYCO-CLEAN 10. Apply once or twice the stripped floor and allow to dry
- Gives ideal foundation for all work process.
- AS SEALER Apply 3 or 4 layers to the stripped floor with a mop or suffient sprayer and wipe with a damp mop daily
- To remove possible foot marks use LEYCO-SEAL 22 diluted with water 1:1.
- Use high speed machines and brown pads. In case of heavy contamination with soilng, grease and oil, floors to be cleaned completely. For basic stripping of substrates from polymer or wax LEYCO-CLEAN 10 is recommended for use.

SAFETY PRECAUTIONS:

Avoid long skin contacts. If accidently splashed into eyes, flush with plenty of water.

STORAGE:

Protect against frost (For 1 year).

PACKAGES:

1L.4L and 15L.

